



## Technical details carpet tiles

Manufacturing type	Herstellungsart	Mode fabrication	Productie methode		<b>ultratuft 1/10"</b>		
Construction	Struktur	Structure	Structuur		<b>loop pile</b>		
Pile composition	Polmateriaal	Couche d'usure	Poolsamenstelling		<b>100% PA 6</b>		
Dye method	Farbgestaltung	Coloration	Kleurverwerking		<b>solution dyed</b>		
Primary backing	Trägermaterial	Premier dossier	Tuftdoek		<b>polyester fleece</b>		
Secondary backing	Rückenausrüstung	Dossier	Rug		<b>GREENBASE modified bitumen</b>		
Pile weight	Poleinsatzgewicht	Poids de velour	Poolgewicht	ISO 2424	g/m <sup>2</sup>	<b>550</b>	(+/-)
Total weight	Gesamtgewicht	Poids total	Totaal gewicht	ISO 8543	g/m <sup>2</sup>	<b>4.100</b>	(+/-)
Pile height	Polhöhe	Hauteur du velours	Poolhoogte	ISO 1766	mm	<b>1,0</b>	(+/-)
Total height	Gesamtdicke	Epaisseur totale	Totale dikte	ISO 1765	mm	<b>5,5</b>	(+/-)
Tuft density	Noppenzahl	Nombre de touffes	Aantal punten	ISO 1763	/m <sup>2</sup>	<b>164.000</b>	(+/-)
Size	Abmessung	Dimension	Afmeting		cm	<b>50 x 50</b>	
Packing	Verpackung	Emballage	Verpakking			<b>20 per box</b>	<b>5 m<sup>2</sup></b>
Classification	Klassifikation	Classement	Gebruiksklasse	EN 1307		<b>33</b>	<b>heavy commercial</b>
Comfort rating	Komfortklasse	Classement confort	Comfort klasse	EN 1307		<b>LC 1</b>	
Castor chair	Stuhlleneignung	Chaise à roulettes	Rolstoelgeschikt	EN 985		<b>A</b>	<b>intensive</b>
Dimensional stability	Dimensionstabilität	Stabilité dimensionnelle	Dimensionele stabiliteit	EN 986		<b>≤ 0,2%</b>	
Fire resistance	Brennverhalten	Comportement feu	Brandgedrag	EN 13501-1		<b>Bfl-S1</b>	<b>loose laid</b>
Permanent antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO 6356	kV	<b>≤ 2,0</b>	
Transversal resistance	Durchgangswiderstand	Résistance transversale	Doorgangsweerstand	ISO 10965	Ω		
Thermal resistance	Wärmedurchlaßwiderstand	Résistance thermique	Warmtedoorlaatweerstand	ISO 8302	m <sup>2</sup> /K/W		
Sound absorption	Schallabsorptionsgrad	Absorption phonique	Geluidsabsorptie	ISO 354	α <sub>w</sub>		
Impact sound reduction	Trittschallverbesserungsmaß	Isolation phonique	Geluidsisolatie	ISO 10140	ΔL <sub>w</sub>		
					ISO 10140	ΔL	(1000 Hz)
Light fastness	Lichtechtheit	Solidité à la lumière	Lichtechtheid	ISO 105 B02		<b>8</b>	
Rubbing fastness	Reibechtheit	Solidité au frottement	Wrijftechtheid	ISO 105 X12		<b>4 - 5</b>	<b>wet/dry</b>
Water fastness	Wasserechtheit	Solidité à l'eau	Waterechtheid	ISO 105 E01		<b>5</b>	<b>colour/staining</b>

Scan the QR code and go to the productpage on the website.



**EN1307**  
for use as floorcovering  
in buildings (EN 14041)  
according to the  
manufacturer's specification

**CE**  
**22**  
**EN 14041**  
**DOP 000495T-001**

