


Technical details needlepunch

Manufacturing type	Herstellungsart	Mode fabrication	Productie methode		needlepunch		
Construction	Struktur	Structure	Structuur		rib		
Pile composition	Polmaterial	Couche d'usure	Poolsamenstelling		100% PP		
Dye method	Farbgestaltung	Coloration	Kleurverwerking		solution dyed		
Secondary backing	Rückenausrüstung	Dossier	Rug		latex		
Pile weight	Poleinsatzgewicht	Poids de velour	Poolgewicht	ISO 2424	g/m ²	310	(+/-)
Total weight	Gesamtgewicht	Poids total	Totaal gewicht	ISO 8543	g/m ²	375	(+/-)
Pile height	Polhöhe	Hauteur du velours	Poolhoogte	ISO 1766	mm	2,5	(+/-)
Size	Abmessung	Dimension	Afmeting		cm	200/400	(+/-)
Classification	Klassifikation	Classement	Gebruiksklasse	EN 1307			
Comfort rating	Komfortklasse	Classement confort	Comfort klasse	EN 1307		LC 1	
Castor chair	Stuhlleneignung	Chaise à roulettes	Rolstoelgeschikt	EN 985			
Stair suitability	Treppeneignung	Escaliers	Trappengeschikt	EN 1963			
Fire resistance	Brennverhalten	Comportement feu	Brandgedrag	EN 13501-1		Bfl-S1	
Permanent antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO 6356	kV	≤ 2,0	
Transversal resistance	Durchgangswiderstand	Résistance transversale	Doorgangsweerstand	ISO 10965	Ω	≥ 10¹⁰	
Thermal resistance	Wärmedurchlaßwiderstand	Résistance thermique	Warmtedoorlaatweerstand	ISO 8302	m ² /K/W		
Sound absorption	Schallabsorptionsgrad	Absorption phonique	Geluidsabsorptie	ISO 354	α _w		
Impact sound reduction	Trittschallverbesserungsmaß	Isolation phonique	Geluidsisolatie	ISO 10140	ΔL _w	16 dB	
				ISO 10140	ΔL	(1000 Hz)	
Light Fastness	Lichtechtheit	Solidité à la lumière	Lichtechtheid	ISO 105 B02		≥ 4	
Rubbing fastness	Reibechtheit	Solidité au frottement	Wrijftechtheid	ISO 105 X12		≥ 3-4	

Scan the QR code and discover the collection.



EN 1307
for use as floorcovering
in buildings (EN 14041)
according to the
manufacturer's specification



13
EN 14041
DOP 000015A-001