


Technical details needlepunch

| | | | | | | |
|------------------------|-----------------------------|-------------------------|-------------------------|-------------|---------------------|--------------------------|
| Manufacturing type | Herstellungsart | Mode fabrication | Productie methode | | | needlepunch |
| Construction | Struktur | Structure | Structuur | | | rib |
| Pile composition | Polmaterial | Couche d'usure | Poolsamenstelling | | | 100% PP |
| Dye method | Farbgestaltung | Coloration | Kleurverwerking | | | solution dyed |
| Secondary backing | Rückenausrüstung | Dossier | Rug | | | latex |
| Pile weight | Poleinsatzgewicht | Poids de velour | Poolgewicht | ISO 2424 | g/m ² | 310 (+/-) |
| Total weight | Gesamtgewicht | Poids total | Totaal gewicht | ISO 8543 | g/m ² | 375 (+/-) |
| Pile height | Polhöhe | Hauteur du velours | Poolhoogte | ISO 1766 | mm | 2,5 (+/-) |
| Size | Abmessung | Dimension | Afmeting | | cm | 100/200/300/400 |
| Classification | Klassifikation | Classement | Gebruiksklasse | EN 1307 | | |
| Comfort rating | Komfortklasse | Classement confort | Comfort klasse | EN 1307 | | LC 1 |
| Castor chair | Stuhlrolleneignung | Chaise à roulettes | Rolstoelgeschikt | EN 985 | | |
| Stair suitability | Treppeneignung | Escaliers | Trappengeschikt | EN 1963 | | |
| Fire resistance | Brennverhalten | Comportement feu | Brandgedrag | EN 13501-1 | | Eff1 |
| Permanent antistatic | Permanent Antistatisch | Antistatique permanent | Permanent antistatisch | ISO 6356 | kV | ≤ 2,0 |
| Transversal resistance | Durchgangswiderstand | Résistance transversale | Doorgangsweerstand | ISO 10965 | Ω | ≥ 10¹⁰ |
| Thermal resistance | Wärmedurchlaßwiderstand | Résistance thermique | Warmtedoorlaatweerstand | ISO 8302 | m ² /K/W | |
| Sound absorption | Schallabsorptionsgrad | Absorption phonique | Geluidsabsorptie | ISO 354 | α _w | |
| Impact sound reduction | Trittschallverbesserungsmaß | Isolation phonique | Geluidsisolatie | ISO 10140 | ΔL _w | 16 dB |
| | | | | ISO 10140 | ΔL | (1000 Hz) |
| Colour fastness light | Lichtechtheit | Solidité à la lumière | Lichtechtheid | ISO 105 B02 | | ≥ 4 |
| Rubbing fastness | Reibechtheit | Solidité au frottement | Wrijftechtheid | ISO 105 X12 | | ≥ 3-4 |

Scan the QR code and discover the collection.



EN1307
for use as floorcovering
in buildings (EN 14041)
according to the
manufacturer's specification

CE
16
EN 14041
DOP 000035N-001