

Technical details needlepunch

Manufacturing type	Herstellungsart	Mode fabrication	Productie methode	needlepunch		
Pile type	Art des Flors	Aspect	Pooltype	Diloop		
Special treatment BAYGARD	BAYGARD imprägniert	Traité BAYGARD	Speciale behandeling BAYGARD	No		
Dye method	Farbgestaltung	Coloration	Kleurverwerking	solution dyed		
Pile content	Polmaterial	Surface	Poolmateriaal	100% Polypropylene		
Secondary backing	Rückenausrüstung	Dossier	Rug	Fire Retardant		
Pile weight	Polersatzgewicht	Poids de velour	Poolgewicht	ISO 2424	g/m ²	350 (+/-)
Total weight	Gesamtgewicht	Poids total	Totaal gewicht	ISO 8543	g/m ²	600 (+/-)
Pile height	Polhöhe	Hauteur du velours	Poolhoogte	ISO 1766	mm	2,0 (+/-)
Width	Lieferbreite	Largeur	Breedte		cm	200/400 (+/-)
Classification	Klassifikation	Classement	Gebruiksklasse	EN 1307		
Comfort rating	Komfortklasse	Classement confort	Comfort klasse	EN 1307		
Castor chair	Stuhrolleneignung	Chaise à roulettes	Rolstoelgeschikt	EN 985		
Stair suitability	Treppeneignung	Escaliers	Trappengeschikt	EN 1963		
Fire resistance	Brennverhalten	Comportement feu	Brandgedrag	EN 13501-1		CF-S1
Permanent antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO 6356	kV	≤ 2,0
Transversal resistance	Durchgangswiderstand	Résistance transversale	Doorgangsweerstand	ISO 10965	Ω	≥ 10¹⁰
Thermal resistance	Wärmedurchlaßwiderstand	Résistance thermique	Warmtedoorlaatweerstand	ISO 8302	m ² /K/W	
Sound absorption	Schallabsorptionsgrad	Absorption phonique	Geluidsabsorptie	ISO 354	α _w	
Impact sound reduction	Trittschallverbesserungsmaß	Isolation phonique	Geluidsisolatie	ISO 140-8	ΔL _w	16 dB
				ISO 10140	ΔL	
Light Fastness	Lichtechtheit	Solidité à la lumière	Lichtechtheid	ISO 105 B02		≥ 4
Rubbing fastness	Reibechtheit	Solidité au frottement	Wrijfchtheid	ISO 105 X12		3-4
Bleach resistance	Chlorechtheit	Resistance au chlor	Chloorbestendig			yes

Scan the QR code and discover the collection.



EN 13297
for use as floorcovering
in buildings (EN 14041)
according to the
manufacturer's specification



EN 14041
DOP 800002