



Technical details carpet tiles

| | | | | | | |
|------------------------|-----------------------------|--------------------------|--------------------------|-------------|---------------------|-----------------------------------|
| Manufacturing type | Herstellungsart | Mode fabrication | Productie methode | | | tufted 1/10" |
| Construction | Struktur | Structure | Structuur | | | cut pile |
| Pile composition | Polmateriaal | Couche d'usure | Poolsamenstelling | | | 100% PA 6 SDN |
| Dye method | Farbgestaltung | Coloration | Kleurverwerking | | | solution dyed |
| Primary backing | Trägermaterial | Premier dossier | Tuftdoek | | | polyester fleece |
| Secondary backing | Rückenausrüstung | Dossier | Rug | | | Greenbase modified bitumen |
| Pile weight | Poleinsatzgewicht | Poids de velour | Poolgewicht | ISO 2424 | g/m ² | 700 (+/-) |
| Total weight | Gesamtgewicht | Poids total | Totaal gewicht | ISO 8543 | g/m ² | 4.300 (+/-) |
| Pile height | Polhöhe | Hauteur du velours | Poolhoogte | ISO 1766 | mm | 4,5 (+/-) |
| Total height | Gesamtdicke | Epaisseur totale | Totale dikte | ISO 1765 | mm | 7,0 (+/-) |
| Tuft density | Noppenzahl | Nombre de touffes | Aantal punten | ISO 1763 | /m ² | 198.750 (+/-) |
| Size | Abmessung | Dimension | Afmeting | | cm | 50 x 50 |
| Packing | Verpackung | Emballage | Verpakking | | | 12 per box 3 m² |
| Classification | Klassifikation | Classement | Gebruiksklasse | EN 1307 | | 33 heavy commercial |
| Comfort rating | Komfortklasse | Classement confort | Comfort klasse | EN 1307 | | LC 2 |
| Castor chair | Stuhllolleneignung | Chaise à roulettes | Rolstoelgeschikt | EN 985 | | A intensive |
| Dimensional stability | Dimensionstabilität | Stabilité dimensionnelle | Dimensionele stabiliteit | EN 986 | | ≤ 0,2% |
| Fire resistance | Brennverhalten | Comportement feu | Brandgedrag | EN 13501-1 | | Bfl-S1 loose laid |
| Permanent antistatic | Permanent Antistatisch | Antistatique permanent | Permanent antistatisch | ISO 6356 | kV | ≤ 2,0 |
| Transversal resistance | Durchgangswiderstand | Résistance transversale | Doorgangsweerstand | ISO 10965 | Ω | ≤ 10⁹ |
| Thermal resistance | Wärmedurchlaßwiderstand | Résistance thermique | Warmtedoorlaatweerstand | ISO 8302 | m ² /K/W | 0,068 |
| Sound absorption | Schallabsorptionsgrad | Absorption phonique | Geluidsabsorptie | ISO 354 | α _w | 0,15 |
| Impact sound reduction | Trittschallverbesserungsmaß | Isolation phonique | Geluidsisolatie | ISO 10140 | ΔL _w | 28 dB |
| | | | | | ISO 10140 | ΔL |
| Colour fastness light | Lichtechtheit | Solidité à la lumière | Lichtechtheid | ISO 105 B02 | | 8 |
| Colour fastness light | Lichtechtheit | Solidité à la lumière | Lichtechtheid | ISO 105 B02 | | ≥ 7-8 |
| Rubbing fastness | Reibechtheit | Solidité au frottement | Wrijftechtheid | ISO 105 X12 | | ≥ 4-5 |

Wall-to-wall

Scan the QR code for the technical details of wall-to-wall.



EN1307
for use as floorcovering
in buildings (EN 14041)
according to the
manufacturer's specification

CE
24
EN 14041
DOP 000665T-001

