

# GAMMA EXTREME

Technical details carpet tiles					
Manufacturing type	Herstellungsart	Mode fabrication	Productie methode	<b>needlepunch</b>	
Construction	Struktur	Structure	Structuur	<b>flat</b>	
Pile composition	Polmaterial	Couche d'usure	Poolsamenstelling	<b>100% PP</b>	
Dye method	Farbgestaltung	Coloration	Kleurverwerking	<b>solution dyed</b>	
Secondary backing	Rückenausrüstung	Dossier	Rug	<b>Bitume</b>	
Pile weight	Poleinsatzgewicht	Poids de velour	Poolgewicht	ISO 2424	g/m <sup>2</sup> <b>900</b> (+/-)
Total weight	Gesamtgewicht	Poids total	Totaal gewicht	ISO 8543	g/m <sup>2</sup> <b>4.200</b> (+/-)
Pile height	Polhöhe	Hauteur du velours	Poolhoogte	ISO 1766	mm <b>5,0</b> (+/-)
Total height	Gesamtdicke	Epaisseur totale	Totale dikte	ISO 1765	mm <b>6,5</b> (+/-)
Size	Abmessung	Dimension	Afmeting	cm	<b>100 x 100 / 50 x 50</b>
Packing	Verpackung	Emballage	Verpakking		<b>50 x 50 cm - 20 per box - 5m<sup>2</sup></b> <b>100 x 100 cm - pallet - 160 m<sup>2</sup>/pallet</b>
Classification	Klassifikation	Classement	Gebruiksklasse	EN 1307	<b>33</b>
Comfort rating	Komfortklasse	Classement confort	Comfort klasse	EN 1307	<b>LC 1</b>
Castor chair	Stuhlrolleneignung	Chaise à roulettes	Rolstoelgeschikt	EN 985	<b>Class A</b>
Fire resistance	Brennverhalten	Comportement feu	Brandgedrag	EN 13501-1	<b>Bfl-S1</b>
Permanent antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO 6356	kV <b>≤ 2,0</b>
Transversal resistance	Durchgangswiderstand	Résistance transversale	Doorgangsweerstand	ISO 10965	Ω <b>≥ 10<sup>10</sup></b>
Thermal resistance	Wärmedurchlaßwiderstand	Résistance thermique	Warmtedoorlaatweerstand	ISO 8302	m <sup>2</sup> /K/W
Sound absorption	Schallabsorptionsgrad	Absorption phonique	Geluidsabsorptie	ISO 354	α <sub>w</sub>
Impact sound reduction	Trittschallverbesserungsmaß	Isolation phonique	Geluidsisolatie	ISO 10140	ΔL <sub>w</sub>
				ISO 10140	ΔL <b>21 dB</b> (1000 Hz)
Light fastness	Lichtechtheit	Solidité à la lumière	Lichtechtheid	ISO 105 B02	<b>≥ 5</b>
Rubbing fastness	Reibechtheit	Solidité au frottement	Wrijftechtheid	ISO 105 X12	<b>3-4</b>

Scan the QR code  
and discover the  
collection.



**EN 1307**  
for use as floorcovering  
in buildings (EN 14041)  
according to the  
manufacturer's specification

**CE**  
**25**  
**EN 14041**  
**DOP 000677T-001**

